



1-072DST DST Clamping Latch



DST

Advantages

- Mini clamping latch with indicator red/green.
- The indicator stays visible and is not concealed in any fitted situation.
- ~6mm compression stroke. (1.)
- In open position the indicator shows "red".
- By turning the knob, the cam is put into the latched position and the "green" indicator appears. Once latched, a further turning of the knob makes the cam start its compression feature.
- RH / LH application.
- Installation by a simple push into the cutout.
- Hand turning knob operated.

Materials

- **Housing, sleeve:** zinc die, matte chrome plated or black coated
- **Insert:** steel, matte chrome plated or black coated
- **Washers:** steel, zinc plated
- **Spring:** stainless steel
- **Cam and snap wedges:** sintered steel, zinc plated

Remarks

1. open, indicator red
2. open, indicator red
3. cam latched, not pulled-down, indicator green
4. cam pulled-down, closed, indicator green



Mini Compression Latch

Part Number	Insert	Clamping range (S)	Surface	Installation type	Delivery Unit
448-9007.00-00810	Hand turning knob	0.8 - 1.0 mm	matte chrome plated	tool-less	1 pcs.
448-9007.00-01113	Hand turning knob	1.1 - 1.3 mm	matte chrome plated	tool-less	1 pcs.
448-9007.00-01416	Hand turning knob	1.4 - 1.6 mm	matte chrome plated	tool-less	1 pcs.
448-9014.00-00810	Hand turning knob	0.8 - 1.0 mm	black	tool-less	1 pcs.
448-9014.00-01113	Hand turning knob	1.1 - 1.3 mm	black	tool-less	1 pcs.
448-9014.00-01416	Hand turning knob	1.4 - 1.6 mm	black	tool-less	1 pcs.

