



1-132 Quarter-Turn Pr20.1 L18/40 for Padlock



Advantages

- Quarter-turn for cutout 20.1.
- IP66 according to DIN EN 60529.
- RH / LH application
- Grounding by grounding nut.
- A pre-assembled quarter-turn can be installed in the cutout.

Materials

- **Wing knob:** zinc die, chrome plated or black
- **Housing:** zinc die, zinc plated
- **Grounding nut:** zinc die

Remarks

(S) Door-thickness see table
Please configure the quarter-turn with a cam.
Padlock feature only if cam is at 90° to the wing knob.
1. seal



Quarter-Turn, zinc die, for padlock

	Part Number	Surface	Version	Housing length	Door-thickness (S)	Installation type	Delivery Unit
a)	200-9365.00-00000	black	E-coated	18 mm	max. 8 mm	screw-on	1 pcs.
a)	100-9311.00-00000	black	E-coated	40 mm	max. 30 mm	screw-on	1 pcs.
a)	200-9365.TX-00000	black	Textured powder, black	18 mm	max. 8 mm	screw-on	1 pcs.
a)	100-9311.TX-00000	black	Textured powder, black	40 mm	max. 30 mm	screw-on	1 pcs.
a)	200-9364.00-00000	chrome plated		18 mm	max. 8 mm	screw-on	1 pcs.
a)	100-9310.00-00000	chrome plated		40 mm	max. 30 mm	screw-on	1 pcs.



Assembly options

200-0020.00-00000 **Assembling cam, LH door**

200-0021.00-00000 **Assembling cam, RH door**



Accessories

b) 1-102 **Cams L35/45 Steel**

b) 1-262 **Cams variable**

