



1-155.01 Quarter-Turn with L-Handle Pr20.1 L30-60



Advantages

- Quarter-turn with L-handle with extended housing and plain/grounding nut.
- Maximum door-thickness 50mm.
- All versions of L-handles are supplied complete with housing.
- Versions **without cylinder** are water and dust tight according to IP65 DIN EN 60529.
- Versions **with cylinder** are water and dust tight according to IP54 DIN EN 60529.
- All lockable handles supplied with 2 keys

Materials

- **Handles:** PA, black with zinc die core or zinc die, chrome plated or black
- **Housing:** zinc die, chrome plated or black
- **Flat external seal:** NBR, black
- **Grounding nut:** zinc die

Remarks

(S) Door-thickness see table
Please configure the quarter-turn with a cam.
1. grounding nut



Quarter-Turn with L-handle, PA, black

	Part Number	Housing length	Latching type	Door-thickness (S)	IP protection	Installation type	Delivery Unit
a)	200-9404.00-00000	30 mm		max. 20 mm	IP65	screw-on	1 pcs.
b)	200-9407.00-00000	30 mm	keyed alike DIRAK 1333	max. 20 mm	IP54	screw-on	1 pcs.
b)	500-9407.00-00000	30 mm	keyed alike DS200	max. 20 mm	IP54	screw-on	1 pcs.
b)	200-9410.00-00000	30 mm	keyed different	max. 20 mm	IP54	screw-on	1 pcs.
a)	200-9405.00-00000	40 mm		max. 30 mm	IP65	screw-on	1 pcs.
b)	200-9408.00-00000	40 mm	keyed alike DIRAK 1333	max. 30 mm	IP54	screw-on	1 pcs.
b)	500-9408.00-00000	40 mm	keyed alike DS200	max. 30 mm	IP54	screw-on	1 pcs.
b)	200-9411.00-00000	40 mm	keyed different	max. 30 mm	IP54	screw-on	1 pcs.
a)	200-9406.00-00000	50 mm		max. 40 mm	IP65	screw-on	1 pcs.
b)	200-9409.00-00000	50 mm	keyed alike DIRAK 1333	max. 40 mm	IP54	screw-on	1 pcs.
b)	500-9409.00-00000	50 mm	keyed alike DS200	max. 40 mm	IP54	screw-on	1 pcs.
b)	200-9412.00-00000	50 mm	keyed different	max. 40 mm	IP54	screw-on	1 pcs.
a)	200-9414.00-00000	60 mm		max. 50 mm	IP65	screw-on	1 pcs.
b)	200-9415.00-00000	60 mm	keyed alike DIRAK 1333	max. 50 mm	IP54	screw-on	1 pcs.
b)	500-9415.00-00000	60 mm	keyed alike DS200	max. 50 mm	IP54	screw-on	1 pcs.
b)	200-9416.00-00000	60 mm	keyed different	max. 50 mm	IP54	screw-on	1 pcs.

Quarter-Turn with L-handle, zinc die, chrome plated

	Part Number	Housing length	Door-thickness (S)	Latching type	IP protection	Installation type	Delivery Unit
a)	200-9439.00-00000	30 mm	max. 20 mm		IP65	screw-on	1 pcs.
b)	200-9443.00-00000	30 mm	max. 20 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	200-9447.00-00000	30 mm	max. 20 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9443.00-00000	30 mm	max. 20 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9447.00-00000	30 mm	max. 20 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9440.00-00000	40 mm	max. 30 mm		IP65	screw-on	1 pcs.
b)	200-9444.00-00000	40 mm	max. 30 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	500-9444.00-00000	40 mm	max. 30 mm	keyed alike DS200	IP54	screw-on	1 pcs.
b)	200-9448.00-00000	40 mm	max. 30 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9444.00-00000	40 mm	max. 30 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9448.00-00000	40 mm	max. 30 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9441.00-00000	50 mm	max. 40 mm		IP65	screw-on	1 pcs.
b)	200-9445.00-00000	50 mm	max. 40 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	200-9449.00-00000	50 mm	max. 40 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9445.00-00000	50 mm	max. 40 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9449.00-00000	50 mm	max. 40 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9442.00-00000	60 mm	max. 50 mm		IP65	screw-on	1 pcs.
b)	200-9446.00-00000	60 mm	max. 50 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	200-9450.00-00000	60 mm	max. 50 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9446.00-00000	60 mm	max. 50 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9450.00-00000	60 mm	max. 50 mm	PAGODA keyed different	IP54	screw-on	1 pcs.

Quarter-Turn with L-handle, zinc die, black

	Part Number	Housing length	Door-thickness (S)	Latching type	IP protection	Installation type	Delivery Unit
a)	200-9451.00-00000	30 mm	max. 20 mm		IP65	screw-on	1 pcs.
b)	200-9455.00-00000	30 mm	max. 20 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	200-9459.00-00000	30 mm	max. 20 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9455.00-00000	30 mm	max. 20 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9459.00-00000	30 mm	max. 20 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9452.00-00000	40 mm	max. 30 mm		IP65	screw-on	1 pcs.
b)	200-9456.00-00000	40 mm	max. 30 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	500-9456.00-00000	40 mm	max. 30 mm	keyed alike DS200	IP54	screw-on	1 pcs.
b)	200-9460.00-00000	40 mm	max. 30 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9456.00-00000	40 mm	max. 30 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9460.00-00000	40 mm	max. 30 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9453.00-00000	50 mm	max. 40 mm		IP65	screw-on	1 pcs.
b)	200-9457.00-00000	50 mm	max. 40 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	500-9457.00-00000	50 mm	max. 40 mm	keyed alike DS200	IP54	screw-on	1 pcs.
b)	200-9461.00-00000	50 mm	max. 40 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9457.00-00000	50 mm	max. 40 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9461.00-00000	50 mm	max. 40 mm	PAGODA keyed different	IP54	screw-on	1 pcs.
a)	200-9454.00-00000	60 mm	max. 50 mm		IP65	screw-on	1 pcs.
b)	200-9458.00-00000	60 mm	max. 50 mm	keyed alike DIRAK 1333	IP54	screw-on	1 pcs.
b)	500-9458.00-00000	60 mm	max. 50 mm	keyed alike DS200	IP54	screw-on	1 pcs.
b)	200-9462.00-00000	60 mm	max. 50 mm	keyed different	IP54	screw-on	1 pcs.
b)	501-9458.00-00000	60 mm	max. 50 mm	PAGODA keyed alike	IP54	screw-on	1 pcs.
b)	501-9462.00-00000	60 mm	max. 50 mm	PAGODA keyed different	IP54	screw-on	1 pcs.

* Accessories

- c) 1-102 **Cams L35/45 Steel**
- c) 1-262 **Cams variable**

