



6-115 Polyamide Lock Cover



Advantages

- For PHZ or KABA-cylinders and quarter-turns.
- 180° Opening angle.
Polyamide lock covers d) and e): **170° Opening angle, spring-loaded cover.**
- Cover is locked by quarter-turn with bolt.

Materials

- **Lower part, cover and base plate:** PA, RAL 7032, RAL 7035 or RAL 9003
Wing knob: PA or brass, nickel plated
- **Shaft:** stainless steel or steel, zinc plated
- **Spring:** stainless steel



Polyamide Lock Cover

	Part Number	Application	Surface	Securable	Wing knob	Version	Screwing type	Delivery Unit
a)	237-9001.00-00000	for PHZ	pebbel grey RAL 7032		PA	shaft: stainless steel	with countersunk holes	10 pcs.
a)	237-9031.00-00000	for PHZ	signal white RAL 9003		PA	shaft: stainless steel	with countersunk holes	10 pcs.
a)	237-9051.00-00000	for PHZ	light grey RAL 7035		PA	shaft: stainless steel	with countersunk holes	10 pcs.
a)	237-9101.00-00000	for PHZ	pebbel grey RAL 7032	Yes	brass, nickel plated	shaft: stainless steel	with countersunk holes	10 pcs.
a)	237-9002.00-00000	for round cylinder Ø22 or quarter-turn housing Ø28	pebbel grey RAL 7032		PA	shaft: stainless steel	with countersunk holes	10 pcs.
a)	237-9102.00-00000	for round cylinder Ø22 or quarter-turn housing Ø28	pebbel grey RAL 7032	Yes	brass, nickel plated	shaft: stainless steel	with countersunk holes	10 pcs.
b)	237-8031.00-00000	for PHZ	signal white RAL 9003		PA	shaft: stainless steel	with blind holes Ø3.1	10 pcs.
c)	237-9103.00-00000	for PHZ	pebbel grey RAL 7032	Yes	brass, nickel plated	shaft: stainless steel	with bushings M4	10 pcs.
c)	237-8004.00-00000	for round cylinder Ø22 or quarter-turn housing Ø28	light grey RAL 7035		brass, nickel plated	shaft: steel, zinc plated	with bushings M4	10 pcs.
c)	237-9154.00-00000	for round cylinder Ø22 or quarter-turn housing Ø28	light grey RAL 7035	Yes	brass, nickel plated	shaft: stainless steel	with bushings M4	10 pcs.
d)	237-8002.00-00000	for PHZ	pebbel grey RAL 7032		without, spring loaded	shaft: stainless steel	with countersunk holes	10 pcs.
d)	237-9303.00-00000	for round cylinder Ø22 or quarter-turn housing Ø28	pebbel grey RAL 7032		without, spring loaded	shaft: stainless steel	with countersunk holes	10 pcs.
e)	237-9304.00-00000	for PHZ	pebbel grey RAL 7032		without, spring loaded	shaft: stainless steel	with countersunk holes	10 pcs.

Spacer

	Part Number	Application	Version	Surface	Delivery Unit
f)	237-0401.06-07032	for Ø22, PHZ	5mm thick	pebbel grey RAL 7032	10 pcs.
f)	237-0401.06-07035	for Ø22, PHZ	5mm thick	light grey RAL 7035	10 pcs.
f)	237-0401.06-09003	for Ø22, PHZ	5mm thick	signal white RAL 9003	10 pcs.
f)	237-0402.06-07032	for PHZ	2mm thick	pebbel grey RAL 7032	10 pcs.

