



6-1680 Machine Handle for Sliding Doors



Advantages

- Sliding door handle for machine equipment.
- By pulling on the handle, the hooked cam is disengaged and the lock released.
- Hooked cam with free stroke.
- Mechanical separation of the handle and the hooked cam.
- As handles any Ø30mm tubes in variable lengths can be used.
- The top and bottom latching devices can be used with or without hooked cam.
- For low or smaller doors, also possible with one hooked cam element.

Materials

- **Tube housing:** zinc die, black
- **Pins:** brass
- **Spring:** stainless steel
- **Hooked cam:** steel, zinc plated
- **Handle-tube:** steel tube with synthetic coating, black

Remarks

1. alternative cutout
 2. open position
 3. closed position
 4. stroke 9mm
- A = distance between the center of the cutouts of the endpieces.



Latching device

	Part Number	Version	Delivery Unit
a)	280-9001.00-00000	with hooked cam	1 pcs.
b)	280-9002.00-00000	without hooked cam	1 pcs.
c)	280-9003.00-00000	with hooked cam	1 pcs.
d)	280-9004.00-00000	without hooked cam	1 pcs.

*** Accessories**

- z) 213-0401.00-00000 **Steel tube, 266mm**
- z) 213-0402.00-00000 **Steel tube, 366mm**
- z) 213-0403.00-00000 **Steel tube, 466mm**
- z) 213-0404.00-00000 **Steel tube, 566mm**
- z) 213-0405.00-00000 **Steel tube, 666mm**
- z) 213-0406.00-00000 **Steel tube, 766mm**



