



## 7-095.01 Quarter-Turn with L-Handle Pr20.1 L30/50 Stainless Steel



### Advantages

- Quarter-turn with L-handle with extended housing.
- IP65 according to DIN EN 60529.
- RH / LH application.
- Grounding by single sided grounding nut.
- Pre-assembled without cam.
- All lockable handles supplied with two keys.

### Materials

- **Handle:** AISI 316, satin polished
- **Housing, grounding nut and adapter:** stainless steel
- **Flat external seal:** NBR, black

### Remarks

1. flat external seal  
Please configure the Quarter-turn with a cam.  
Price and delivery time on request.  
Maximum door-thickness 20mm / 40mm.  
Further housing lengths on request.



## Quarter-Turn with L-handle

	Part Number	Housing length	Latching type	Door-thickness (S)	Installation type	Delivery Unit
a)	100-9407.00-00000	30 mm		max. 20 mm	screw-on	1 pcs.
b)	100-9408.00-00000	30 mm	keyed alike DIRAK 1333	max. 20 mm	screw-on	1 pcs.
b)	100-9409.00-00000	30 mm	keyed different	max. 20 mm	screw-on	1 pcs.
a)	100-9410.00-00000	50 mm		max. 40 mm	screw-on	1 pcs.
b)	100-9411.00-00000	50 mm	keyed alike DIRAK 1333	max. 40 mm	screw-on	1 pcs.
b)	100-9412.00-00000	50 mm	keyed different	max. 40 mm	screw-on	1 pcs.



## Assembly options

200-0001.00-00000 **Assembling cam without o-ring**

200-0019.00-00000 **Assembling cam 90° to handle without o-ring**

200-0020.00-00000 **Assembling cam, LH door**



## Accessories

- c) 1-102 **Cams L35/45 Steel**
- c) 7-105 **Cams L35/45 Stainless Steel**
- c) 1-262 **Cams variable**

